| TECHNICL NOTES            |  |  |  |  |  |
|---------------------------|--|--|--|--|--|
| NOTES                     | CONTENT  |  |  |  |  |
| GENERAL NOTES             |  |  |  |  |  |
| Metal structure treatment | Iron structures should be painted to prevent rust and improve equipment life.          |  |  |  |  |
|                           | - Remove loose rust with a wire brush, sandpaper or chemical rust remover.             |  |  |  |  |
|                           | - If applicable, sand areas where paint is chipping until surface is smooth.           |  |  |  |  |
|                           | - Remove dust or oil with a degreaser or denatured alcohol.                            |  |  |  |  |
|                           | - Prime surface to protect against rust and corrosion                                  |  |  |  |  |
| Wood treatment            | - The wood must be treated with pesticides and kiln-dried to ensure adequate humidity. |  |  |  |  |
|                           | - Wood sealer should be applied for later use.   |  |  |  |  |

| PROJECT                                    | CREATED BY               | APPROVED BY                              | DATE       | VERSION        |
|--|--------------------------|--|------------|----------------|
| Scooter with fat tire<br>PART NAME         | J. Rosciano<br>FILE NAME | A. Morillo                               | 31/08/2021 | 1.2<br>POS     |
| Technical notes DEVELOPED BY REDESIGNED BY |                          | DOC. TYPE MATERIAL<br>Technical<br>notes |            | C1<br>QUANTITY |
|  |                          | LICENCE                                  | SCALE      | SHEET          |
| ОНО  | OHO e.V.                 | CC-BY-SA 4.0                             |            | 7 /65          |