


TECHNICAL NOTES

| NOTES | CONTENT |
|---------------------------|---|
| GENERAL NOTES | |
| Metal structure treatment | Iron structures should be painted to prevent rust and improve equipment life. - Remove loose rust with a wire brush, sandpaper or chemical rust remover. - If applicable, sand areas where paint is chipping until surface is smooth. - Remove dust or oil with a degreaser or denatured alcohol. - Prime surface to protect against rust and corrosion |
| Wood treatment | - The wood must be treated with pesticides and kiln-dried to ensure adequate humidity. - Wood sealer should be applied for later use. |
| ... | ... |
| ... | ... |

| | | | | |
|----------------------------|---|-----------------|------------|----------|
| PROJECT | CREATED BY | APPROVED BY | DATE | VERSION |
| Sovonius rotor 1m diameter | D.MOSQUERA | A. MORILLO | 22/10/2021 | 1.0 |
| PART NAME | FILE NAME | | | POS |
| Technical notes | | | | C1 |
| DEVELOPED BY | REDESIGNED BY | DOC. TYPE | MATERIAL | QUANTITY |
| Josef Hagmann, Austria |  | Technical notes | | |
| | | LICENCE | SCALE | SHEET |
| | | CC-BY-SA 4.0 | | 5 /17 |

OHO e.V.