TECHNICL NOTES					
NOTES	CONTENT				
GENERAL NOTES					
Metal structure treatment	Iron structures should be painted to prevent rust and improve equipment life.				
	- Remove loose rust with a wire brush, sandpaper or chemical rust remover.				
	- If applicable, sand areas where paint is chipping until surface is smooth.				
	- Remove dust or oil with a degreaser or denatured alcohol.				
	- Prime surface to protect against rust and corrosion				
Foundations fixing	- The ground must be stable and have a low water table.				
	- The structure must be fixed on firm oncrete soil or on poured footings with steel reinforcement.				
	- The anchorage can be bolted with expansive ramplugs or welded.				
Wood treatment	- The wood must be treated with pesticides and kiln-dried to ensure adequate humidity.				
	- Wood sealer should be applied for later use.				

PROJECT	CREATED BY	APPROVED BY	DATE	VERSION	
Savonius rotor two level	D. MOSQUERA	A. MORILLO	07/10/2021	1.0	
PART NAME	FILE NAME			POS	
Technical notes				C1	
DEVELOPED BY REI	DESIGNED BY	DOC. TYPE MATERIAL		QUANTITY	
		Technical			
		notes			
4		LICENCE	SCALE	SHEET	
		2			
		CC-BY-SA 4.0		7 /44	

TECHNICL NOTES									
NOTES	CONTENT								
DIAGRAM X									
DESCRIPTION		Innover	ICDEATED BY	TARRED DV	IDATE	TVEDSTON.			
		Savonius rotor two level PART NAME Technical notes DEVELOPED BY	CREATED BY D. MOSQUERA FILE NAME	APPROVED BY A. MORILLO DOC. TYPE MATERIAL Technical	07/10/2021	1.0 POS C2 QUANTITY			
				> notes o LICENCE O CC-BY-SA 4.0	SCALE	SHEET 8 /44			