TECHNICL NOTES						
NOTES	CONTENT					
GENERAL NOTES						
Metal structure treatment	Iron structures should be painted to prevent rust and improve equipment life.					
	- Remove loose rust with a wire brush, sandpaper or chemical rust remover.					
	- If applicable, sand areas where paint is chipping until surface is smooth.					
	- Remove dust or oil with a degreaser or denatured alcohol.					
	- Prime surface to protect against rust and corrosion					
Foundations fixing	- The ground must be stable and have a low water table.					
	- The structure must be fixed on firm oncrete soil or on poured footings with steel reinforcement.					
	- The anchorage can be bolted with expansive ramplugs or welded.					
Wood treatment	- The wood must be treated with pesticides and kiln-dried to ensure adequate humidity.					
	- Wood sealer should be applied for later use.					

PROJECT		CREATED BY	APPROVED BY		DATE	VERSION
Vertical Axis Sail Windmill		D. Mosquera	A. Morillo		12/07/2021	1.0
PART NAME		FILE NAME				POS
Technical notes						C1
		GNED BY	DOC. TYPE	MATERIAL		QUANTITY
			Technical			
			notes		-	
			LICENCE		SCALE	SHEET
		PEN SOURCE ECOLOGY GERMANY				
Low Energy Systems OSEC			CC-BY-SA 4.0			6 /27